

## SLZ12V300S LiFePO4 12V 300Ah

### **SPECIFICATION / TECHNICAL SHEET**

Specification	s	
•		12.8V
Nominal Voltage		
Nominal Capacity (25°C, 0.33C)		300Ah
Dimensions	Length	520±3mm
	Width	269±3mm
	Height	222±3mm
	Total Height	222±3mm
Approx. Weight		39.0kg
Characteristi	cs	
Terminal type		M8
Max Charge Voltage		14.6V±0.2V
Standby Voltage		13.8±0.2V
Cut-off Voltage		10V
Max. Discharge Current		200A
Max Pulse Discharge Current (3 sec)		450A
Max Charge Current		200A
Recommended Charge Current		< 150A
Cycle Life (100% DoD)		1800+
Operating Temp - Charge		0°C - 45°C
Operating Temp - Discharge		-20°C - 60°C
Short Circuit Release		Yes
Max. Series / Parallel Configuration		4S / 4P
Cell Type		Prismatic
Cell Chemistry		Lithium Iron Phosphate (LiFePO4)
BMS Protection		Yes
Warranty		3 Years

#### Applications

- Deep-cycle
- 4x4 Vehicles
- Recreational Vehicles
- Caravan / Camping
- Fast Recharge Requirements
- Low Weight Applications
- Marine
- Golf Carts
- Personal Power
- Non-Starting

#### About Zeal Lithium

Zeal lithium is an economical 12V Lithium Iron Phosphate (LiFePO<sub>4</sub>) solution by Sealed Performance Batteries (SPB) which provides the core performance and safety advantages of a modern lithium battery in a well-built design.

Backed by SPB, a company with over 25 years of experience in the energy storage industry, and designed to the best possible specifications, you can be confident that Zeal lithium has had every detail thoroughly examined in delivering a high-value solution.

#### Safe And Stable

Zeal provides a high degree of safety by utilising light-weight aluminum encased LiFePO<sub>4</sub> prismatic cells, which and among the safest and most stable lithium cells available.

It is also supported by an integrated BMS that protects against overcharge/discharge, temperature and short circuit events for complete confidence when in operation.

#### **Core Lithium Advantages**

A perfect AGM replacement, Zeal comes complete with a 3 year warranty and all the features you would expect from a LiFePO4 product including fast recharge capabilities, low self-discharge rate, long runtime and more usable capacity for power when you need it most.

Need a larger solution? Up to 4 batteries can also be connected in parallel or series configurations to meet the needs of more demanding systems.

# L. SPB

SPB National Head Office: 1 Ant Road, Yatala, Brisbane, QLD 4207, Australia
SPB Melbourne Office: 2/9 Compark Circuit, Mulgrave, VIC, 3170, Australia
SPB Sydney Office: 1/1 Forge Street, Blacktown, NSW, 2148, Australia
T 1300 001 772 E info@spb.net.au W spb.net.au