			Conditions
cell type:		NiMH	
cell size:		AA	
nominal voltage:	1.2	V	
max. charge voltage:	1.5	V	at standard charge (0.1C / 20℃)
capacity			
nominal:	800	mAh	discharge at 0.2C
minimum:	800	mAh	discharge at 0.2C
	750	mAh	discharge at 1C 1.0V end discharge voltage ta: 20℃
max. continuous discharge current:	2400	mA	ta: 0....45℃
charge	current		time
standard charge:	80	mA	14....16hrs
quick charge:	240	mA	4hrs
fast charge:	800	mA	1.1hrs
recommended charge termination control parameters:	0…5	mV	- ΔV (-deltaV)
	0.8...1	℃	temperature rise per minute
	45...50	℃	TCO (temperature cut off)
trickle charge current:	5…25	mA	(recommended)
continuous overcharge: (less than 1 year)	≤ 80	mA	no conspicuous deformation no leakage
internal resistance: (impedance)	≤ 50	mΩ	at 1KHz battery fully charged
life expectance:	≥ 500	cycles	acc. IEC standard
self discharge			
charge retention:	≥ 80	%	after 12 months storage at 20℃
initial capacity:	≥ 550	mAh	within 30 days after delivery discharge at 0.2C
ambient temperature range:	0...45	℃	standard charge
	10...40	℃	fast charge
	0...45	℃	discharge (≥1C)
	- 20...65	℃	discharge (<1C)
	- 20...50	℃	storage (≤3months)
	- 20...40	℃	storage (≤6months)
	- 20...30	℃	storage (≤24months)
QCT1:	20/750/50		
QCT2:	30/700/55		

Diagrams

standard charge



fast charge



low rate discharge



high rate discharge



mechanical specifications

cell dimensions			
diameter d1:		14.3 - 0.7	mm
diameter d2:	max.	5.5	mm
height h1:		50.4 - 0.5	mm
height h2:	min.	1.2	mm
weight:		17 ± 2	g
blister card dimensions:		123 x 85	mm
blister card weight (incl. batteries):		42	g



	ANSMANN Specifications for model:	AA - 800mAh low self discharge SOLAR 2pcs blister package
	data sheet no. / part no.	5035513
	supplier no.	702069
	author / date	Gramlich / 13.02.2012

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice